

the DNV-certified IBC transport frame has passed extensive design and performance testing for strength, durability, and safety and meets all requirements of DNV 2.7-1 for offshore applications. Transport frames can be used to safely transport standard 120 to 793 gallons (454 to 3,000 liters) Intermediate Bulk Containers or other IBCs in an offshore environment.



### DESCRIPTION

- DNV-certified frame meets all requirements of DNV 2.7-1 or DNV 2.7-3.
- Lifting capabilities: Four (4) DNV pad eyes. Product complies with all applicable DNV standards and regulations
- 4-legged sling assembly with 45° sling angle
- Removable hold-down bars secure IBCs into the frame
- Front loading design
- Fork lift channels: 4-way fork lift entry

- Safe for offshore transportation
- DNV certified lifting frame
- DNV certified slings
- DNV certified pad eyes
- Marine-grade paint coating
- Load tested
- NDT/MPI tested

### AVAILABLE SIZES

Metric international standard

Container Type	External dimensions (LxWxH - mm)	Tare weight (kgs)	Payload (kgs)	Max gross weight (kgs)
550 US Gallon IBC	1067 x 1219 x 1905	286 kg	3,964 kg	4,250 kg

Availability on demand

**CARGOWELD®**  
800 77 RENTA